






THE MG GROUP



Hospitality Appliances Pvt. Ltd.



MG-PRO

REACH IN UPRIGHT REFRIGERATORS / FREEZERS

Machine	Description		
2 Door Refrigerator	Dimension	742(L)x853(D)x2152(H) mm	
	Cooling	Forced Air (No Frost)	
	Doors	01 No. half / 02 Nos. full SS solid doors	
	Construction	S.S.304 Interior and Exterior S.S. Base and Back	
	Capacity	530(Lits)	
	Power	550 Watts	
	Refrigerant	R 134a	
	Temperature Range	+2°C to +4°C	
	Amps drawn	3	
	Feet	Nylon bullet feet	
	Shelves per door	02 Nos of SS rod shelves	
2 Door Deep Freezer (No frost)	Dimension	742(L)x853(D)x2152(H) mm	
	Cooling	Forced Air (No Frost)	
	Doors	01 No. half / 02 Nos. full SS solid doors	
	Construction	S.S.304 Interior and Exterior S.S. Base and Back	
	Capacity	530(Lits)	
	Power	560 Watts	
	Refrigerant	R 134a	
	Temperature Range	-10°C to -14°C	
	Amps drawn	4	
	Feet	Nylon bullet feet	
	Shelves per door	02 Nos of SS rod shelves	
4 Door Refrigerator	Dimension	1422(L) x 853(D) x 2152(H)	
	Cooling	Forced Air (No Frost)	
	Doors	02 Nos. half / 04 Nos. full SS solid doors	
	Construction	S.S.304 Interior and Exterior S.S. Base and Back	
	Capacity	1090(Lits)	
	Power	1025 Watts	
	Refrigerant	R 134a	
	Temperature Range	+2°C to +4°C	
	Amps drawn	3.6	
	Feet	Nylon bullet feet	
	Shelves per door	02 Nos of SS rod shelves	

4 Door Freezer			
Dimension		1422(L) x 853(D) x 2152(H)	
Cooling		Static	
Doors		02 Nos. half / 04 Nos. full SS solid doors	
Construction		S.S.304 Interior and Exterior G.I. Base and Back	
Capacity		1090(Lits)	
Power		650 Watts	
Refrigerant		R 134a	
Temperature Range		-15°C to -18°C	
Amps drawn		4	
Feet		Nylon bullet feet	
Shelves per door		02 Nos of SS rod shelves	
Four Door Twin Tank Static Dual Temp (single compressor)			
Dimension		1422(L) x 853(D) x 2152(H)	
Cooling		Static	
Doors		02 Nos. half / 04 Nos. full SS solid doors	
Construction		S.S.304 Interior and Exterior S.S. Base and Back	
Capacity		1130 Ltrs	
Power		700 Watts	
Refrigerant		R 134a	
Temperature Range		-10° C to -18° C	
Temperature Range		+2° C to +4° C	
Feet		Nylon bullet feet	
Shelves per door		02 Nos of SS rod shelves	

NOTE:

Material construction is in Pre- polished PVC coated AISI 304 SS exterior and interior, back and bottom in SS
 Ext body: 20G, Inside: 22G, Doors: 18G,
 Legs: 38mm 16G round pipes and Frame work: 32mm Square pipe
 Imported door handles.
 Imported press type door gaskets.
 Coved Corners
 Digital Temperature Controller with On delay .
 Environment friendly Refrigerants.
 Spring loaded self closing hinges.
 SS Rod shelves.
 Adjustable Nylon Bullet Feet
 All refrigeration equipment require adequate ventilation for efficient and effective performance.
 70 mm ODP zero PU foam for excellent thermal efficiency
 Anti condensation heaters fitted to door mullions
 Refrigeration system with low noise making and highly energy efficient compressors

OPTIONAL / EXTRA:

Swivel / brake castors
 SS bullet feet
 Light - Local
 Glass doors