






THE MG GROUP

Hospitality Appliances Pvt. Ltd.




MG-PRO

Under - Counter REFRIGERATORS / FREEZERS

Machine	Description	
1 Door Refrigerator	<p>Dimension 955(L) x 748(D) x 864(H)mm</p> <p>Cooling Forced Air (No Frost)</p> <p>Door 01 No. of SS solid doors</p> <p>Construction S.S.304 Interior and Exterior S.S. Base and Back. Mono-block Type <i>Removable Condensing Unit for easy</i></p> <p>Capacity 150(Lits)</p> <p>Power 300 Watts</p> <p>Refrigerant R 134a</p> <p>Temperature Range +2°C to +4°C</p> <p>Amps drawn 3</p> <p>Feet Nylon bullet feet</p> <p>Shelves per door 02 Nos of SS rod shelves</p>	
2 Door Refrigerator	<p>Dimension 1415(L) x 748(D) x 864(H)mm</p> <p>Cooling Forced Air (No Frost)</p> <p>Door 02 Nos. of SS solid doors</p> <p>Construction S.S.304 Interior and Exterior S.S. Base and Back. Mono-block Type <i>Removable Condensing Unit for easy</i></p> <p>Capacity 290(Lits)</p> <p>Power 425 Watts</p> <p>Refrigerant R 134a</p> <p>Temperature Range +2°C to +4°C</p> <p>Amps drawn 2.6</p> <p>Feet Nylon bullet feet</p> <p>Shelves per door 02 Nos of SS rod shelves</p>	
3 Door Refrigerator	<p>Dimension 1870(L) x 748(D) x 864(H)mm</p> <p>Cooling Forced Air (No Frost)</p> <p>Door 03 Nos. of SS solid doors</p> <p>Construction S.S.304 Interior and Exterior S.S. Base and Back. Mono-block Type <i>Removable Condensing Unit for easy</i></p> <p>Capacity 450(Lits)</p> <p>Power 550 Watts</p> <p>Refrigerant R 134a</p> <p>Temperature Range +2°C to +4°C</p> <p>Amps drawn 4</p> <p>Feet Nylon bullet feet</p> <p>Shelves per door 02 Nos of SS rod shelves</p>	

4 Door Refrigerator

Dimension	2330(L) x 748(D) x 864(H)mm
Cooling	Forced Air (No Frost)
Door	04 Nos. of SS solid doors
Construction	S.S.304 Interior and Exterior S.S. Base and Back. Mono-block Type <i>Removable Condensing Unit for easy maintenance</i>
Capacity	610(Lits)
Power	1025 Watts
Refrigerant	R 134a
Temperature Range	+2°C to +4°C
Amps drawn	4.5
Feet	Nylon bullet feet
Shelves per door	02 Nos of SS rod shelves



NOTE:

Material construction is in Pre polished PVC coated AISI 304 SS exterior and interior, back and bottom in SS
Work Tops: 18G, Ext body: 20G, Inside: 22G, Doors: 18G,
Legs: 38mm 16G round pipes and Frame work: 32mm Square pipe
Imported Drawer Sliders of 50 Kgs load bearing capacity.
Imported door handles.
Imported press type door gaskets.
Coved Corners
Digital Temperature Controller with On delay .
Environment friendly Refrigerants.
Spring loaded self closing hinges.
SS Rod shelves.
Adjustable Nylon Bullet Feet
All refrigeration equipment require adequate ventilation for efficient and effective performance.
70 mm ODP zero PU foam for excellent thermal efficiency
Anti condensation heaters fitted to door mullions
Refrigeration system with low noise making and highly energy efficient compressors

OPTIONAL / EXTRA:

Swivel / brake castors
Light - Local
Light- LED
SS Bullet feet
Glass doors
Available with refrigerated (ventilated) raised pan holder of 150 mm height
Available with standard top cut out
Available with set of 2 or 3 drawers
Available with back splash and / or sides splash